DECLARATION OF PERFORMANCE

No: FE 4890

1. Unique identification code of the product type: **FE 4890**

2. Intended use: Skylights for use in unheated, uninhabited spaces in buildings

3. Manufacturer: Altaterra Kft., Hungary, 9431 Fertőd, Malom köz 1. www.altaterra.eu

5. Systems of assessment and verification of constancy of performance (AVCP): System 3

6a. Harmonised standard: EN 14351-1:2006+A2:2016
Notified body/ies[1]: 0757, 1415

7. Declared performance:

Essential Characteristics	Performance	NB[1]
Resistance to wind load[2]	B3	0757
Resistance to snow load[3]	3-8-3	
Reaction to fire	B s1,d0	1415
External fire performance	Broof (t1)	1415
Watertightness	2A	0757
Impact resistance	npd	
Load-bearing capacity of safety devices	npd	
Acoustic performance (R_w)	npd (dB)	
Thermal transmittance (U_w)[4]	npd (W/m^2K)	
Solar factor (g)	npd	
Light transmittance (τ_w)	npd	
Air permeability	npd	

npd: No Performance Determined
[1]: Notified body/ies: http://ec.europa.eu/growth/tools-databases/nando/
[2]: For window width > 1140 mm or window height > 1398 mm: npd
[3]: Layers from outside to inside. H: toughened, HS: heat-strengthened
[4]: The communicated value refers either to the tested size 114/134 x 140 cm in vertical position according to the EN 12567-2 standard or in case of calculation 123 x 148 cm in vertical position according to the EN 10077-1/2 standard.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Krzysztof Dudek, CEO
Fertőd, Hungary on 05/08/2013



altaterra

CE 13	**FE 4890** **Skylights for use in unheated, uninhabited spaces in buildings**	**Harmonised standard EN 14351-1:2006 +A2:2016**
Essential Characteristics	**Performance**	**NB**
Resistance to wind load(2)	B3	0757
Resistance to snow load(3)	3-8-3	
Reaction to fire	B s1,d0	1415
External fire performance	Broof (t1)	1415
Watertightness	2A	0757
Impact resistance	npd	
Load-bearing capacity of safety devices	npd	
Acoustic performance (R_w)	npd (dB)	
Thermal transmittance (U_w)(4)	npd (W/m^2K)	
Solar factor (g)	npd	
Light transmittance (τ_w)	npd	
Air permeability	npd	

npd: No Performance Determined

1 : Notified body/ies: http://ec.europa.eu/growth/tools-databases/nando/

2 : For window width > 1140 mm or window height > 1398 mm: npd

3 : Layers from outside to inside. H: toughened, HS: heat-strengthened

4 : The communicated value refers either to the tested size 114/134 x 140 cm in vertical position according to the EN 12567-2 standard or in case of calculation 123 x 148 cm in vertical position according to the EN 10077-1/2 standard.